

Characterizations of Cathode Pad Chamber as tracking detector for MUON Spectrometer of ALICE

By

Sanjoy Pal

**SAHA INSTITUTE OF NUCLEAR PHYSICS
Kolkata**



*A thesis submitted to the
Board of Studies in Physical Science Discipline
In partial fulfillment of requirements
For the Degree of
DOCTOR OF PHILOSOPHY
of
HOMI BHABHA NATIONAL INSTITUTE*



November, 2008

Contents

1	Introduction	1
1.1	Introduction	1
1.2	Standard Model and Quark Gluon Plasma	2
1.3	Theoretical and Phenomenological overview of QGP phase transition	5
1.4	Space-time evolution of the heavy-ion collision	11
1.5	Geometry of heavy-ion collisions	13
1.6	Kinematic Variables	14
1.7	Experimental observables	17
1.7.1	Hadron radiation	18
1.7.2	Electromagnetic probes	21
1.7.3	Strangeness enhancement	22
1.7.4	Jet quenching	24
1.7.5	Heavy quarkonia suppression	26
2	ALICE Detector and Dimuon Spectrometer	37
2.1	Overview	37
2.2	Central Barrel Detectors	39
2.2.1	Inner Tracking System(ITS)	39
2.2.2	Time Projection Chamber (TPC)	40
2.2.3	Time Of Flight (TOF) detector	42
2.2.4	Transition-Radiation Detector (TRD)	43
2.2.5	High-Momentum Particle Identification Detector	43
2.2.6	Photon Spectrometer (PHOS) Detector	44
2.2.7	Electromagnetic Calorimeter (EMCal)	45
2.3	Forward Detectors	45
2.3.1	Multiplicity Detector	45
2.3.2	Zero-Degree Calorimeters (ZDC)	47
2.4	Dimuon Spectrometer	48
2.4.1	Front absorber	51
2.4.2	Small angle absorber	52
2.4.3	Dipole magnet	53
2.4.4	Tracking system	53
2.4.5	Muon Filter	55
2.4.6	Trigger system	55

3	Second Tracking Station	59
3.1	Overview	59
3.2	Cathode Pad Chamber	60
3.2.1	Energy loss and Ionization in Detector	61
3.2.2	Choice of the gas mixture	63
3.2.3	Motion of electron and ion in gases	64
3.2.4	Principle of operation	67
3.2.5	Anode wire plane	71
3.2.6	Cathode Segmentation	74
3.3	The Design details	76
3.3.1	The Frames	77
3.3.2	The Rib	80
3.3.3	Anode PCB	81
3.3.4	Cathode PCB	83
3.3.5	The Kapton PCB	86
3.3.6	The Rohacell	87
3.3.7	The mechanical exit board	88
3.3.8	The Central Point Fixation	89
3.3.9	Support strip for anode wire	90
3.3.10	Assembly Procedure	91
3.4	Chamber Testing	92
3.4.1	Flatness Test of the Cathode plane	92
3.4.2	Elasticity of the chamber	93
3.4.3	Gas leak rates measurement of the chamber	94
3.4.4	The high voltage stability test	95
3.4.5	The Gain measurement of the Chamber	96
4	Readout Electronics	103
4.1	Overview	103
4.2	Electronic Exit Board	108
4.3	MANAS	113
4.3.1	Charge Sensitive Amplifier (CSA)	114
4.3.2	Deconvolution Filter (DF)	116
4.3.3	Semi-Gaussian Shaping Filter (SGS)	117
4.3.4	Track and Hold (T/H) and the Analog Multiplexer	118
4.3.5	Input Protection	120
4.3.6	Design Specifications	120
4.3.7	Test Bench setup for final version of MANAS	123
4.3.8	MANAS (Production batch) Testing	124
5	In-Beam Test	147
5.1	Overview	147
5.2	Test at CERN PS	147
5.2.1	Noise and pedestal distribution	148
5.2.2	Gain study	152

5.2.3	Gain Calibration of MANAS channel on MANU cards	155
5.2.4	Resolution Studies	156
5.3	Test at CERN SPS	162
5.3.1	MANAS gain calibration	164
5.3.2	Results	166
6	Installation and Commissioning of Second Tracking Station	171
6.1	Overview	171
6.2	Pre-installation Tests at CERN	172
6.2.1	High Voltage stability Test	172
6.2.2	Readout Electronic Validation Test	176
6.3	Chamber Installation	181
6.4	Commissioning Tests	183
6.4.1	Gas flow tests	183
6.4.2	High Voltage Tests	184
6.4.3	Electronic readout test	185
6.5	Cosmic Muon Measurement	188
7	Implementation of detector geometry and Mapping in Aliroot.	193
7.1	Overview	193
7.2	Raw data format for the MUON Tracking	195
7.3	Mapping	199
7.4	Geometry	203
7.5	Signal Generation	206
8	Summary	211